

# Access Platforms

## Our 8m Electric Driven Access

### SWSL08 DC Scissor Lift [8m]

The SWSL08 DC Scissor Lift has been designed to help users accomplish tasks such as installing glazing, cladding, signage, steel, timber frames and more, with ease. Operators can stay safe and work efficiently at up to 8m high with minimal disruption to the surrounding area.

This versatile MEWP has a platform height of 6m and an overall working height of 8m making it ideal for a variety of different projects. With a lifting capacity of 230kg and a maximum occupancy of 2 people, this nimble machine is the perfect addition to your fleet or is available to hire from GGR Group.

Boasting an overall width of just 760mm and stowed height of 2170mm, this mini machine is compact enough to fit into the smallest of spaces including hospitals, shopping centres recycling plants, train stations, office buildings and more.

The SWSL08 DC has a small 1670mm turning radius with its dual front wheel drive, which makes it handy to have in tight spaces or when completing lifting projects on sites that have a small working area.

#### Reference Code

**SWSL08DC**



#### Technical Specifications

<b>Max platform height</b>	6m
<b>Max working height</b>	8m
<b>Platform length</b>	1700mm
<b>Platform width</b>	740mm
<b>Capacity</b>	230kg
<b>Extension capacity</b>	113kg
<b>Drive speed</b>	0.8km/h (elevated), 4.5km/h (stowed)
<b>Turning radius</b>	0mm (inside), 1670mm (outside)
<b>Raise/lower speed</b>	20s / 27s
<b>Gradeability</b>	25%
<b>Max working angle</b>	1.5° (lateral), 3° (longitudinal)
<b>Battery</b>	4x6V/225Ah
<b>Charger</b>	24V/30Ah
<b>Weight</b>	2100kg

The non marking tyres allow the SWSL08 DC Scissor Lift to be used in sites with sensitive flooring



A moveable joystick allows the operator free control to move, rise and lower the MEWP either on or at the base of the platform



Easy diagnostics are possible thanks to the in-built USB port where a smartphone can be used to problem solve



The long-life batteries ensure a long run-time between charging as well as having zero emissions and a low noise output

Foldable rails means the compact SWSL08 Scissor Lifts can reduce their stowed height even further from 2170mm to 1790mm



The maximum platform height of 6m gives users a maximum working height of 8m, giving a good balance of compactness and reach



### Key Features

- Capacity: 230kg (main platform), 113kg (extending platform)
- Dimensions: 1860mm (l) x 760mm (w) x 2170mm (h)
- Turning radius: 1670mm (outside), 0mm (inside)
- Maximum occupancy: 2 people
- Non marking tyres
- Tilt sensor with alarm
- Pothole protection
- Dual front wheel drive
- Weight: 2100kg



The SWSL08 DC comes fitted with a self-locking gate for operator safety



Lifting eyes are included for ease of transport or moving from level to level by crane.

### Technical Data (approx. mm)

