# A Unique New Self-Leve

# Multi-Loader 3.0 BL [3000kg]

The battery-operated Multi-Loader 3.0 BL is the perfect tool for moving goods up to 3000 kg over difficult terrain.

The Multi-Loader 3.0 BL uses a special Bi-Levelling technology for optimal control and manoeuvrability when working in confined spaces and on busy construction sites. Even while moving over inclines and uneven terrain, its automated self-levelling load-deck guarantees maximum control in the safe delivery of cargo.

This environmentally friendly carrier has a 48v rechargeable battery and works both indoors and out. It can also move across horizontal slopes of up to 25° and vertical slopes of up to 25°.

The ML 3.0 BL Tracked Leveller has a class-leading electric drive with two 5.3kW extremely quiet IP67-rated AC electric motors, and it has three power management modes with varying speeds. It can be configured with AGM or lithium batteries.

Glass, machinery, lumber and other commodities can all be transported on site with the help of the Multi-Loader 3.0 BL. Plus with the optional non-marking tracks the fully electric ML 3.0 BL is perfectly suited for working in places such as shopping centres, rail stations and other locations with sensitive environments.

#### **Reference Codes**

AGM Battery Code: TPS 3.0 ABL LTH Battery Code: TPS 3.0 LBL

# **Technical Specifications**

	ELC	LIH	
Capacity	3000kg		
Min width	1460mm		
Max width	1640mm		
Min height	740mm		
Length	2400mm		
Longitudinal levelling front	20°		
Longitudinal levelling rear	15°		
Lateral levelling	+/- 14°		
Gradeability	25°		
Side slope	25°		
Max speed	4.2km/h		
Electric motor power	2 x 5.3kW		
Voltage	48V		
Battery charger	No <sup>2</sup> 65-48V (110/220v)		
Battery pack	Lead Crystal No <sup>8</sup> 180Ah 48V	210Ah - 48V	
Recharging time	3.5hr - 65A	3.5hr - 65A	
IP protection	IP67		
Weight	1855kg	1670kg	









### **Power Mode Load Examples**

<b>Power Mode</b>	Load			Max Speed
	0kg	1500kg	3000kg	
ECO	~4500m	~3800m	~3200m	1.2km/h
STD	~4200m	~3400m	~2700m	1.8km/h
POW	~3900m	~3000m	~2200m	4.2km/h



The Multi-Loader 3.0 BL features an optional tow bar accessory.





The Multi-Loader 3.0 BL optional ramp kit allows the easy loading of wheeled or tracked equipment.

The Multi-Loader 3.0 BL approaches the load to be lifted from underneath with it's low profile height of 740mm.

Once in place, the Multi-Loader 3.0 BL can raise up which at the same time narrows the width from 1640mm to 1460mm.


The Multi-Loader 3.0 BL can raise and lower from 740mm to a maximum height of 1070mm.


Then it can be driven away and using its dynamic auto-levelling can traverse gradients of up to 20°, keeping the load flat & stable.
















The Multi-Loader 3.0 BL features automatic dynamic self-levelling technology to enaure the stability of the load.



## **Key Features**

- Capacity: 3000kg
- Maximum/minimum width: 1640mm / 1460mm
- Automatic dynamic self-levelling
- Three driving modes: Main / ED-S / DC-S
- Three power management modes: ECO / STD / PWR
- Automatic tilt alarm with speed reduction
- Auxiliary hydraulic sockets
- Maximum gradeability: 25°
- Controlled by radio remote
- Only 3.5 hours to fully charge
- Maximum speed: 4.2km/h
- Weight: 1855kg (AGM) / 1670kg (LTH)







The Multi-Loader 3.0 BL is fully controlled by radio remote.

