

Overhang Beams

Our 2500kg Capacity

Libro 2500B [2500kg]

The Libro 2500B is the GGR Group's overhang beam boasting a maximum capacity of 2500kg and is able to install glass, curtain walling and cladding below overhangs of up to 3000mm deep.

Featuring a hook at the end of its lifting arm, the Libro 2500 counterweight balancer can be used with a below-the-hook vacuum lifter, which are also offered for hire or sale from the GGR Group*.

This high capacity overhang beam can be attached to tower cranes or mobile cranes and is suitable for installation projects at height.

Key Features

- 2500kg capacity
- Hook attachment
- Suitable for overhangs up to 3m deep
- 1175kg weight with counterweights, 425kg with counterweights removed
- Cable remote control for counterweight saddle
- 24V DC battery with separate 110/240V charger
- $\pm 10^\circ$ Anti-Tilt Switch

Reference Code

VOB2500B



Libro 2500B fitted with a modified MRTA8 vacuum lifter on a manipulating head for installing GRC soffit panels

Technical Specifications

Safe working load	capacity:	2500kg
Weight of lifter	weight:	1250kg (with counterweights) 500kg (without counterweights)
Depth of overhang	depth:	3000mm
Balance control	control:	rack and pinion counterweight saddle
Power requirements	power:	24V DC rechargeable battery 110/240v battery charger
Standard accessories	standard:	cable remote control to operate counterweight saddle
Optional accessories	optional:	radio remote control

Capacities At Each Working Length

Length (mm)	Capacity (kg)	Weight Trolley Position
1500mm	2500kg	1
1750mm	2000kg	2
2000mm	1600kg	3
2250mm	1300kg	4
2500mm	1050kg	5
2750mm	850kg	6
3000mm	700kg	7

**use of below-the-hook vacuum lifters depend on type of project. Below the hook lifter not included.*

Overhang Beam

Libro 2500B Overhang Beam



Technical Data (mm)

