


URW-094

(0.995t x 1.5m)

- Total width 0.595m
- Max working radius 5.17m
- Petrol powered, optional LPG dual fuel
- Multi-position configurable outriggers
- Intelligent voice warning system
- Radio remote control as standard
- Intelligent throttle activation for economy and ecology




The URW-094 is the world's smallest and lightest mini crane. At only 595mm wide and weighing 1000kg it is ideal for manoeuvring into the most confined working areas and is narrow enough to allow access through a standard doorframe. Once in position, the URW-094 is capable of lifting heavy loads of almost 1 tonne with its 5.49m long boom allowing a maximum hook height of 5.6m.

ADDITIONAL FEATURES



Radio remote control




CRANE SPECIFICATIONS

Crane capacity	capacity:	0.995t x 1.5m
Max. working radius	max:	5.17m
Max. lifting height	approx:	5.6m
Rope length	max:	13.89m (2 fall), 28.77 m (1 fall)
Dimensions	folded:	1870mm (l) x 595mm (w) x 1290mm (h)
Weight	unladen:	1000kg
Point loadings	Due to the many variables involved, point loadings are only available on request	
Hook speed	approx:	8.5m/min (with 3 layers and 2 falls)
Telescopic system	boom length:	1.73 - 5.49m
	telescoping speed:	3.76m/17 seconds
	boom type:	4 sections hydraulically telescoping boom, 4 sided box beam
Derricking angle/speed	approx:	0 - 78° / 6.5 seconds
Slewing angle/speed	approx:	360° (continuous) 1.5 min rpm
Traction system	drive:	hydrostatic, stepless forward and reverse
	travel speed:	0 - 2.2km / h
	gradeability:	20° (vertical), 10° (traverse)
	track ground length:	900mm
	track ground pressure:	36.3kPa (0.37kg/cm²)
Engine	track width:	150mm
	manufacturer:	Mitsubishi
	fuel:	petrol (LPG dual option)
	maximum output:	5.5kW (75PS) / 1800 min rpm
	starting method:	electric and recoil start as standard
Standard equipment	tank capacity:	6 litres
	radio remote control, overwinding alarm, computer controlled intelligent voice warning system, multi-function operation by radio remote control, intelligent throttle activation, automatic hook stow	
Optional equipment	1 fall hook block, LPG dual power, low marking tracks	

MINI SPIDER CRANE

UNIC
CRANES EUROPE

MAIN BOOM RATED LOADS WITH OUTRIGGERS SET TO MAX & OUTRIGGER POSITIONS



FIRST STAGE EXTENDED 1.73m BOOM LENGTH

Working radius	m	up to 1.0	1.1	1.2	1.3	1.41
Outrigger	kg	995	995	995	995	995
Min-extended	kg	800	800	750	700	650

SECOND STAGE EXTENDED 1.73 - 3.01m BOOM LENGTH

Working radius	m	up to 1.0	1.1	1.3	1.5	2.0	2.5	2.69
Outrigger	kg	995	995	995	995	800	650	580
Min-extended	kg	800	800	700	600	410	285	230

THIRD STAGE EXTENDED 3.01 - 4.25 m BOOM LENGTH


Working radius	m	up to 1.0	1.8	2.0	2.5	2.8	3.0	3.5	3.93
Outrigger	kg	850	850	800	650	580	530	400	320
Min-extended	kg	500	500	410	285	215	190	145	115

FOURTH STAGE EXTENDED 4.25 - 5.49 m BOOM LENGTH


Working radius	m	up to 2.4	2.5	2.8	3.0	3.5	4.0	4.5	5.1	5.17
Outrigger	kg	660	660	580	530	410	330	270	210	200
Min-extended	kg	360	320	220	190	145	105	80	65	65



DIMENSIONS



OUTRIGGER ANGLE POSITIONS



OPTIONAL LPG GAS

